

Technical specification

SR2075 TS

SR2085 TS

TABLE

Base cutting width	m	4.50	4.80
Optional cutting width	m	4.20/4.80/5.10	4.20/4.50/5.10
Cutting height	m	- 0.20..+1.20	- 0.20..+1.20
Knife speed	strokes/min	1020	1020
Table reverse type/Option		mech./electric.	mech./electric.

PICK-UP REEL

Diameter	m	1.05	1.05
Speed range	rpm	15...49	15...49
Speed adjustment (from the driver seat)		electrical	electrical
For/aft adjustment/Option		mech./electric.	mech./electric.

PRE-THRESHING CYLINDER

Width/diameter	m	1.11/0.40	1.11/0.40
Speed	rpm	600...1300	600...1300
Pre-concave area	m ²	0.34	0.34

THRESHING CYLINDER

Width/diameter	m	1.11/0.50	1.11/0.50
Heavy duty cylinder		standard	standard
Number of rasp bars	pcs	8	8
Type of rasp bars		changeable	changeable
Speed range	rpm	600...1300	600...1300
Option (* same rpm for P-T Cyl.)	rpm	400...1150	400...1150
Speed adjustment		electrical	electrical

CONCAVE

Area	m ²	0.51	0.51
Angle of wrap	°	105	105
Number of bars	pcs	12	12
Stepless adjustment range	mm	6...42	6...42

STRAW WALKERS

Number / steps	pcs	5/4	5/4
Total separation area	m ²	4.80	4.80

SHAKER SHOE

Top sieve, adjustable	m ²	1.74 + 0.33	1.74 + 0.33
Bottom sieve, fixed round holes	m ²	1.33	1.33
Optional bottom sieve		adjustable	adjustable
Total area	m ²	3.40	3.40
Fanning mill adjustment		electrical	electrical

STRAW CHOPPER

Swinging knife type		optional	optional
---------------------	--	----------	----------

GRAIN TANK

Capacity	m ³	5.10	5.10
Discharge height	m	3.40	3.40

ENGINE

Power	kW/hp	110/150	137/185
Optional engine power		137/185, 147/200	110/150, 147/200
Rpm		2200	2200
Number of cylinders (T=turbo)		6T	6T
Dual air filter with ejector pre-cleaning		standard	standard
Fuel injection pump type / Or		Inline/rotary	Inline/rotary
Fuel tank capacity	l.	350	350

TRANSMISSION

	3 -speeds	hydro	hydro
--	-----------	-------	-------

WORKING HYDRAULIC

Master lever		standard	standard
--------------	--	----------	----------

TYRES

Front, standard		520/70R34	600/65R34
Rear, standard		360/70R20	420/65R20

CAB

Optional cab		SR-standard	SR-standard
Driver seat type		Deluxe	Deluxe
Buddy seat		SR-standard	Deluxe
3-speed fresh air ventilator		optional	standard
Heater		standard	standard
Air conditioning		optional	optional
Engine air filter blockage indicator		standard	standard

WEIGHT

With cab and standard cutting table	kg	8400	8600
-------------------------------------	----	------	------

DIMENSIONS

Overall length (without straw dividers)	m	9.10	9.10
Transport height, with SR-cab	m	3.50	3.50
Width with base table	m	4.90	5.20
With less table with std tyres	m	3.04	3.12
Ground clearance	m	0.43	0.43



Sampo-Rosenlew Ltd
Konepajaranta 2 A
FI-28101 PORI, FINLAND
Tel. +358 207 550 555
Fax +358 2 632 6546

www.sampo-rosenlew.fi

Manufacturer reserves right to do changes on machines without notice and without obligation to apply such changes to machines manufactured before. Specifications may vary from country to country. Contact your retailer for current specifications.