

TECHNICAL SPECIFICATIONS

		COMIA C4	COMIA C6	COMIA C8
CUTTING TABLE				
Standard width	m	3,90	4,20	4,50
optional widths	m	3,45/4,20	3,90/4,50	4,20/4,80
Cutting height	m	- 0,20...+1,20	- 0,20...+1,20	- 0,20...+1,20
Knife speed	strokes/min	1020	1020	1020
Header reverse	type	elec.	elec.	elec.
REEL				
Diameter	m	1,05	1,05	1,05
Speed range	rpm	15...49	15...49	15...49
Speed adjustment		elec.	elec.	elec.
Electric for/aft adjustment		std	std	std
PRE-THRESHING CYLINDER				
Width/diameter	m			1,11/0,40
Rate	rpm			600...1300
Concave area	m ²			0,34
THRESHING CYLINDER				
Width/diameter	m	1,11/0,50	1,11/0,50	1,11/0,50
HD -cylinder		std	std	std
Number of rasp bars	pcs	8	8	8
Rasp bar type		changeable	changeable	changeable
Speed range	rpm	600...1300	600...1300	600...1300
Speed adjustment		elec.	elec.	elec.
CONCAVE				
Area	m ²	0,51	0,51	0,51
Angle of wrap	°	105	105	105
Number of rasp bars	pcs	12	12	12
Stepless adj.range	mm	6...42	6...42	6...42
Concave adjustment		stepless	stepless	elec.
STRAW WALKERS				
Number	pcs	4	5	5
Total separation area	m ²	4,80	4,80	4,80
CSP-separating drum		not available	std	std
SHAKER SHOE				
Top sieve	m ²	1,74 + 0,33	1,74 + 0,33	1,74 + 0,33
Bottom sieve	m ²	1,33	1,33	1,33
Total area	m ²	3,40	3,40	3,40
Fan speed adjustment		elec.	elec.	elec.

		COMIA C4	COMIA C6	COMIA C8
STRAW CHOPPER				
Swining knife type		std	std	std
GRAIN TANK				
Capacity	m ³	3,70	4,20	5,20
Discharge height	m	3,40	3,40	3,40
optional	m	4,00	4,00	4,00
ENGINE				
		Sisu Power	Sisu Power	Sisu Power
Power	kW/hv	110/150	136/185	154/210
Rpm/cylinder		2000/4	2000/6	2000/6
Fuel tank capacity	l	200	350	350
TRANSMISSION				
		Hydro	Hydro	Hydro
Final drives		closed final drives	closed final drives	closed final drives
TIRES				
Front		520/70R34	600/65R34	600/65R34
Rear		360/70R20	420/65R20	420/65R20
CAB				
		Premium Plus	Premium Plus	Premium Plus
Seat model		Grammer	Grammer	Grammer
Extra seat		std	std	std
Heater		std	std	std
Air conditioning		option	option	std
Radio/CD		std	std	std
WEIGHT				
Standard header and chopper	kg	7100	8000	9000
DIMENSIONS				
Lenght with std header w/o dividers	m	8,68	8,68	9,10
Transport height	m	3,65	3,65	3,65
Transport width with std header	m	4,30	4,60	4,90
Transport width w/o header with std tires	m	2,96	3,12	3,12
Clearance	m	0,43	0,43	0,43
PLENTY OF OPTIONS AND ACCESSORIES				

The product development of the Sampo Rosenlew combines continues. Therefore the Company reserves the right to modify the products without prior notice and without obligation to make the same modifications to combines previously manufactured. The pictures in this brochure are selected from globally used material, due to which some details may vary from country to country. Check the information with your dealer.