



SAMPO ROSENLEW

HR86



HR86

TECHNICAL SPECIFICATION

WEIGHT & DIMENSIONS	Minimum machine weight	21 000kg	
	Total Length	13 500 mm	
	Base Machine length	8 214 mm	
	Width	2,670 / 2,890 mm	
	Transport height	3 670 mm	
	Wheelbase	4 270 mm	
GROUND CLEARANCE		650 mm	
ENGINE	Acqo Power	74 LFTN	204 kW/1950 rpm, 214 kW/1850 rpm
FUEL TANK		360 l	
TRANSMISSION	Hydrostatic-mechanical	with diff. locks.	
	Speed	0-20 km/h	
	Tractive force	190 kN	
WHEELS	Front and Rear	600/55-26,5 or 710/45-26,5	
HYDRAULICS	Pump	2*165 l / 1000 r/min	
ELECTRICS	Batteries	24 V , 2 X 180 Ah	
WORKING LIGHTS		18 pic	
CRANE	Mesera 240H	10.3 or 11.1 meters reach	
HARVESTER HEAD		Kesla 26RH-III, Kesla 27RH-III, Kesla 28RH-III	
COMPUTER		Technion xLogger / PC	
CABIN	(FOPS;ROPS;OPS)	Rotating and levelling	

