



**SAMPO ROSENLEW**

**HR86**





# HR86

## TECHNICAL SPECIFICATION

<b>WEIGHT &amp; DIMENSIONS</b>	Minimum machine weight	21 000kg
	Total Length	13 500 mm
	Base Machine length	8 214 mm
	Width	2,670 / 2,890 mm
	Transport height	3 670 mm
	Wheelbase	4 270 mm
<b>GROUND CLEARANCE</b>		650 mm
<b>ENGINE</b>	Acgo Power 74 LFTN -D5	204 kW/1950 rpm, 214 kW/1850 rpm
<b>FUEL TANK</b>		360 l
<b>TRANSMISSION</b>	Hydrostatic-mechanical	with diff. locks.
	Speed	0-20 km/h
	Tractive force	190 kN
<b>WHEELS</b>	Front and Rear	600/55-26,5 or 710/45-26,5
<b>HYDRAULICS</b>	Pump	2*165 l / 1000 r/min
<b>ELECTRICS</b>	Batteries	24 V , 2 X 180 Ah
<b>WORKING LIGHTS</b>		18 pic
<b>CRANE</b>	Mesera 240H	10.3 or 11.1 meters reach
<b>HARVESTER HEAD</b>		Kesla 26RH-III, Kesla 27RH-III, Kesla 28RH-III
<b>COMPUTER</b>		Technion xLogger / PC
<b>CABIN</b>	(FOPS;ROPS;OPS)	Rotating and levelling

