



SAMPO ROSENLEW



FR48

FR48

MOTOR	AGCO Power 49 LFTN-D5
Effekt	140 kW @2 100 U/min
Vridmoment	700 Nm @1 100-1 600 U/min
Bränsletank	220 l
DEF-tank	15 l
DRAGKRAFT	170 kN
Växel 1	0 - 8 km/h
Växel 2	0 - 25 km/h
DÄCK	
Framaxel	26.5 in.
Bakaxel	26.5 in.
STYRNING	Proportional
Styrvinkel	+/- 45 °
HYDRAULIK	
Pumpkapacitet	110 cm ³
Flöde	220 l/min @2 000 U/min
Arbetsstryck	21,5 MPa
Hydraultank	125 l
ELSYSTEM	
Spänning	24 V
Batterier	2 x 145 Ah
Generator	100 A
Belysning	17 St.
KRAN	Mesera 83F / Kesla 700
Maximal räckvidd	10 /10,3 m
Brutto lyftmoment	106 / 70 kNm
Svängmoment	26,1/ 24 kNm
Svängvinkel	380 °
GRIP	0,26 - 0,36 m ²
MÄTVÄRDEN	
Längd (A)	9 537/ 9 837/ 10 137 mm
Boggi mitt - midjeled (B)	1 850 mm
Midjeled - boggi mitt (C)	2 970/ 3 270/ 3 570 mm
Hjulbas (B + C)	4 820/ 5 120/ 5 420 mm
Bredd - 700-seriens däck (D)	2 890 mm
Transporthöjd (E)	3 830 mm
Markfrigång (F)	650 mm
Maskinens minimivikt	16 500 kg
LASTUTRYMMESALTERNATIV	
Lastkapacitet	12 000 kg
Totallängd (H)	4 400/4 700/5 000 mm
Bredd lastutrymme (G)	2 680/ 2 850 mm
Lastarea	4,0/ 4,3 m ²

Bitte beachten Sie: Diese Informationen sind nominal und die genauen Zahlen können je nach Herstellungsabweichung variieren.

